

PARAMETERS		VALUE
PHYSICAL PARAMETERS	Pixel Configuration	Black SMD1010
	Pixel Pitch (mm)	1.58
	Pixel Dimensions L x W x H (mm)	610 x 343 x 60
	Pixel Per Panel	384 x 216
	Panel Weight (kg/lbs)	8.5 /18.7
	Panel Material	Die casting Aluminum
	Module Dimensions L x W (mm)	305x343
OPTOELECTRONIC PARAMETERS	Brightness (Nits)	700
	Refresh Rate (Hz)	1920-3840
	Grayscale (Bit)	14
	Contrast Ratio	4000:1
	Color Temperature (K)	7500
	Viewing Angle (H/v) (°)	160/140
	Driving Type	1/24
	AC Operating Voltage (V)	100~240
	Power Consumption (Max. /Avg.) (W/m ²)	610/203
APPLICATION PARAMETERS	Storage Temperature (°C)	- 40~ + 60
	Operating Temperature (°C)	- 10~ + 40
	Storage Humidity (Rh)	10 % ~90 %
	Operating Humidity (Rh)	10 % ~90 %
	IP Rating (Front/Rear)	IP40/IP21
	LED Lifetime (H)	100000
	Module Maintenance	Front
	PSU & Other Maintenance	Front
	Panel Installation Type	Rigging/Stack,Front/Rear Installation
	Rigging Quntity (Vertical)(PCS)	12
	Certifications	TUV-CE+RoHS/ETL+FCC/CCC

All specifications are subject to change without notice.

V.3346.a.170803