



## New A Series

- Meet various medium and high-end outdoor advertising scenarios needs
- Extremely Real Display Performance
- High Stability & Reliability
- Very Low Operating Cost Throughout Product's Life Cycle

### Specification

Parameters	A0421 Common cathode	A0621	A0821
Pixel Pitch(mm)	4.44	6.66	8
Brightness (nit)	7500	10000	10000
Refresh Rate (Hz)	> 3840	> 6000	> 15000
Contrast ratio	7500 : 1	9000 : 1	19000 : 1
Max/Avg Power (w/m <sup>2</sup> )	570/190	660/220	675/225
Panel Dimension	1280 × 960 × 70mm (50.39 × 37.80 × 2.76inch)	1280 × 960 × 72mm (50.39 × 37.80 × 2.83inch)	
IP Rating	IP65/IP54	IP65/IP54	IP65/IP54
Certification		FCC, ETL, CE	

  

	A1021	A1021D	A1621D
Pixel Pitch(mm)	10	10.66	16
Brightness (nit)	10000	10000	10000
Refresh Rate (Hz)	> 15000	> 5000	> 26000
Contrast ratio	22000 : 1	15000 : 1	24000 : 1
Max/Avg Power (w/m <sup>2</sup> )	675/225	260/87	270/90
Panel Dimension	1280 × 960 × 72mm (50.39 × 37.80 × 2.83inch)	1280 × 960 × 80mm (50.39 × 37.8 × 3.14inch)	
IP Rating	IP65/IP54	IP65/IP54	IP65/IP54
Certification		FCC, ETL, CE	



## AW Series

- Exquisite picture quality offering shocking visual experiences
- Fully water resistant panel that performs impeccably in all kinds of extreme weather
- Thin & light die casting panel, easy maintenance
- Efficient heat dissipation prolongs a great service life
- Suitable for right Angle stitching application, bring higher commercial value

## Specification

Parameters	AW2.5	AW2.8	AW3.9
Pixel Pitch(mm)	2.5	2.84	3.9
Brightness (nit)	4500	5000	5000
Refresh Rate (Hz)	≥3840	≥4800	≥3840
Gray Scale (Bit)	15	15	16
Max/Avg Power (w/m <sup>2</sup> )	660/ 220	660/ 220	630/ 210
Panel Dimension	500×500×83mm / 500×750×83mm(19.68×19.68×3.26inch / 19.68×29.52×3.26inch)		
IP Rating	IP65/ IP65	IP65/ IP65	IP65/ IP65
Certification	FCC, ETL, CE	FCC, ETL, CE	FCC, ETL, CE