

Absenicon C Slim

High Screen-to-Body Ratio Screen



98% Screen-to-Body Ratio



Ultra-Slim Frame



600nits Brightness



Easy Installation/ Maintenance

◀ Key Features



Highly Integrated Design

Far more than just a screen, the C Slim screen is highly integrated, including controller, modules, cabinets, installation mounts, cables and all necessary display elements needed for the installation.



Ultra-Slim Frame

With a .2 in ultra-slim frame, the screen-to-body ratio reaches 98%, providing an immersive experience for all the viewers.

- *The upper, left, right and bottom bezel are .2/.2/.2/.91 in respectively
- *The thinnest part of the screen body is only 1.12 in



Refresh Your Vision

Experience stunning visual performance with Absenicon C Slim series. Every dark or bright detail looks vivid and clear with its 110% NTSC level colour gamut and 600nits brightness.



Easy and Reliable Content Sharing

Absenicon supports screen mirroring through computer, mobile phone and PAD screen. The screen share up to 4 devices at one time wirelessly, allowing creativity display simultaneously.



Smart Control

Absenicon brings the connectivity of smart TVs to a larger more dynamic LED display. And multiple functions can be realized through remote control.



Easy Installation and Maintenance

Support wall mounting, mobile stand installation, suitable for different indoor space environment. Simple installation process saves time and labor. In case of the LED module or internal component fails, it can be maintained from the front.

*C165S only supports wall mounted installation

◀ Product Parameters

Parameter	C110S		C138S		C165S	
Diagonal Size (inches)	110"		138"		165"	
Screen Dimensions (W x H)(inches)	96"*54"		120"*67.5"		144"*8"	
Pixel Pitch(mm)	1.27		1.58		1.9	
Screen Dimensions Including Bezel (WxHXD)(in)	96.5"x55"x1.1"		120.5"x68.6"x1.1"		144.5"x81.5"x1.1"	
Screen Resolution (dots)	1920×1080		1920×1080		1920x1080	
Installation	Wall mounting	Mobile stand	Wall mounting	Mobile stand	Wall mounting	
Weight (lb)	258	306	386	434	555	
Aspect Ratio	16:9		16:9		16:9	
Brightness (nit)	600		600		600	
Contrast Ratio	4000:1		5000:1		4000:1	
Grayscale (bit)	14		14		14	
Refresh Rate (Hz)	3840		3840		3840	
Viewing Angle (Horizontal/Vertical)(°)	160/140		160/140		160/140	
Ave./Max. Power Consumption (W)	584/1750		667/2000		800/2400	
Android System	Android 8.0		Android 8.0		Android 8.0	
Processor Core		Main frequency 1.7G 64-bit quad-core processor				
System capacity	4GB+16GB					
Control Interface	MiniUSB*1, RJ45*1					
Input/output Interface	H	HDMI2.0*3, USB2.0*1, USB3.0*1, Audio OUT*1, SPDIF OUT*1, RJ45*1				
Windows System		Optional				
Certification		FCC, CE				

^{*}The thinnest part of the screen body is only 1.12 in



HQ Office

Lake Ellenor Dr Orlando, FL

. info@usabsen.com www.usabsen.com

East Service Center&Warehouse
Presidents Drive, Orlando, FL
West Service Center & Showroom
Valley Blvd Suite J, Walnut, CA







