



## K Plus Series

K1.9 Plus / K2.5 Plus



Lightweight design



Ultra-high performance



Easy installation



Front & rear maintenance

### ◀ Application scenario



Retail



Conference Room



House of Worship

### ◀ Lightweight design, contracted beauty



500\*1000\*62.5mm


11 kg

500\*750\*62.5mm

8.5 kg

## ◀ Installation & maintenance

- Support hanging and stacking installation
- Support full front & rear maintenance of module, power box and receiving card
- Optional back-mounting installation and the overall thickness can reach 8.3cm



Front Install Screw through whole, 240\*70 connection strap



Front Install Screw between panels



Rear Screw Hole



Rear Install Screw

## ◀ Product specification

Parameters	K1.9 Plus	K2.5 Plus	K3 Plus
LED type	Black SMD1515	Black SMD2121	Black SMD2121
Pixel pitch (mm)	1.95	2.6	3.9
Panel dimensions (W*H*D, mm)	500x1000x62.5 / 500x750x62.5		
Brightness (nit)	700	700	700
Refresh rate (Hz)	1920/3840	1920/3840	1920
Grayscale (bit)	14	14	14
Contrast ratio	2500:1	2500:1	4000:1
Color temperature (K)	6500	6500	6500
Viewing angle (H/V, °)	160/160	160/160	160/160
Drive mode	1/64	1/50	1/16
AC operating voltage (V)	100~240	100~240	100~240
Power consumption (max./avg., W/m <sup>2</sup> )	420/140	390/130	300/100
IP Rating (Front/Rear)	IP40/IP21	IP40/IP21	IP40/IP21
Certification	FCC, ETL, CE, RoHS	FCC, ETL, CE, RoHS	FCC, ETL, CE, RoHS

\*The panel supports 90-degree rotating installation if needed, and the module needs to be rotated 90 degrees in the opposite direction



**HQ Office**  
7120 Lake Ellenor Dr Orlando, FL 32809  
407.203.8870 info@usabsen.com  
www.usabsen.com

**East Service Center&Warehouse**  
7307 Presidents Drive, Orlando, FL 32809  
**West Service Center & Showroom**  
20311 Valley Blvd Suite J, Walnut, CA 91789

Twitter: @Absen\_Inc  
 Facebook: @AbsenInc  
 LinkedIn: @AbsenInc  
 IG: @absen\_inc