



## A Series

10000nit High Brightness  
Energy-saving LED Display



High Brightness  
& Energy Saving



Extremely Real  
Display Performance



High Stability  
& Reliability



Very Low Operating Cost  
Throughout Product's Life Cycle

### ◀ High Stability & Reliability

Multi-layered water resistant design involving modules/panels/power boxes to ensure safety.



Professional heat dissipation structure design.  
Free of Fan Design



## ◀ Extremely real display performance

Dazzling and Vivid Images, to make you see the most natural and real world



**Up to 10000nit**  
High Brightness



**3840+ Hz**  
High Refresh Rate



**16bit**  
High Gray Scale



**10000+: 1**  
High Contrast Ratio



**150% BT.709**  
Wide color gamut



**PWM**  
High level driving IC

## ◀ Meet various medium and high-end outdoor advertising scenarios needs



Billboard



Spectacular



Street Furniture



Digital Sign



Transit Center



Sports

## ◀ Very low operating cost throughout product's life cycle



Savings in electricity costs



Thin panel, convenient transport,  
save transport cost



Light weight panel, saving  
steel structure cost



Convenient maintenance-front  
and rear access

## ◀ Product Specification

Model	A1021D	A1621D
LED type	DIP	DIP
Pixel pitch(mm)	10.66	16
Brightness(nit)	10000	10000
Refresh rate(Hz)	≥5000	≥26000
Grayscale(bit)	16	16
Power consumption (Max./Avg. ,W/m <sup>2</sup> )	260-330/87-110	270-330/90-110
Panel dimensions(WxHxD, mm/inch)	1280x960x80mm (50.39x37.8x3.14")	1280x960x80mm (50.39x37.8x3.14")
Panel Weight(kg/lb)	37kg/81.57lb	35kg/77.16lb
Panel material	Aluminum Profile	
IP Rating	IP65 / IP54	
Maintenance	Front/Rear	
Certification	FCC, ETL, CE	

**Absen**

www.usabsen.com  
info@usabsen.com

### HQ Office

7120 Lake Ellenor Drive  
Orlando, FL 32809  
407.203.8870

### Service Center & Warehouse

7307 Presidents Drive  
Orlando, FL 32809  
866-872-2736



Twitter: @Absen\_Inc



Facebook: @AbsenInc



LinkedIn: @AbsenInc



IG: @absen\_inc