



A Series

10000nit High Brightness
Energy-saving LED Display



High Brightness
& Energy Saving



Extremely Real
Display Performance



High Stability
& Reliability



Very Low Operating Cost
Throughout Product's Life Cycle

◀ High Stability & Reliability

Multi-layered water resistant design involving modules/panels/power boxes to ensure safety.



Professional heat dissipation structure design.
Free of Fan Design



◀ Extremely real display performance

Dazzling and Vivid Images, to make you see the most natural and real world



Up to 10000nit
High Brightness



3840+ Hz
High Refresh Rate



16bit
High Gray Scale



10000+: 1
High Contrast Ratio



150% BT.709
Wide color gamut



PWM
High level driving IC

◀ Meet various medium and high-end outdoor advertising scenarios needs



Billboard



Spectacular



Street Furniture



Digital Sign



Transit Center



Sports

◀ Very low operating cost throughout product's life cycle



Savings in electricity costs



Light weight panel, saving steel structure cost



Thin panel, convenient transport, save transport cost



Convenient maintenance-front and rear access

◀ Product Specification

Model	A1021D	A1621D
LED type	DIP	DIP
Pixel pitch(mm)	10.66	16
Brightness(nit)	10000	10000
Refresh rate(Hz)	≥5000	≥26000
Grayscale(bit)	16	16
Power consumption (Max./Avg. ,W/m ²)	260-330/87-110	270-330/90-110
Panel dimensions(WxHxD, mm/inch)	1280x960x80mm (50.39x37.8x3.14")	1280x960x80mm (50.39x37.8x3.14")
Panel Weight(kg/lb)	37kg/81.57lb	35kg/77.16lb
Panel material	Aluminum Profile	
IP Rating	IP65 / IP54	
Maintenance	Front/Rear	
Certification	FCC, ETL, CE	

Absen

www.usabsen.com
info@usabsen.com

HQ Office

7120 Lake Ellenor Drive
Orlando, FL 32809
407.203.8870

Service Center & Warehouse

7307 Presidents Drive
Orlando, FL 32809
866-872-2736



Twitter: @Absen_Inc



Facebook: @AbsenInc



LinkedIn: @AbsenInc



IG: @absen_inc