



## A25 Series

- Energy saving, Less than 1 KWH/SQM per day
- Stability, extend up to 10 years warranty
- 10 second module Install or dismantle, Module Spare Management and Upgrade
- Consistently outstanding display, undisturbed by environment

### Specification

Product	A0425	A0625	A0825	A1025
Pixel pitch (mm)	4.44	6.66	8	10
LED type	SMD1921	SMD2727	SMD2727	SMD2727
Brightness (nit)	7500	7500/10000	7500/10000	7500/10000
Refresh rate (Hz)	≥7680	≥7680	≥15000	≥15000
Grayscale (bit)	16			
Power Consumption (Max./Avg,W/m <sup>2</sup> )	540 135	450/590 112/148	440/580 110/145	440/580 110/145
Panel dimensions (WxHxD,mm/inch)	1280×960×82 mm / 50.4×37.8×3.2"			
Panel resolution(Pixels)	288x216	192x144	160x120	128x96
Panel material	Aluminum			
Weight/Pane (kg/lbs)	35 kg / 77.2 lbs			
Ingress protection	IP66 / IP66			
Maintenance	Rear or Front			
Certification	ETL/FCC/CE/CCC			

\*Source: Absen lab



## A Series

- Meet various medium and high-end outdoor advertising scenarios needs
- Extremely Real Display Performance
- High Stability & Reliability
- Very Low Operating Cost Throughout Product's Life Cycle

## Specification

Parameters	A1021D	A1621D
Model	A1021D	A1621D
LED type	DIP	DIP
Pixel pitch(mm)	10.66	16
Brightness(nit)	10000	10000
Refresh rate(Hz)	≥5000	≥26000
Grayscale(bit)	16	16
Power consumption (Max./Avg. ,W/m <sup>2</sup> )	260-330/87-110	270-330/90-110
Panel dimensions (mm/inch)	1280x960x80mm / 50.39×37.8×3.14"	
(WxHxD, mm/inch)	(50.39x37.8x3.14")	(50.39x37.8x3.14")
Panel Weight(kg/lb)	37kg/81.57lb	35kg/77.16lb
Panel material	Aluminum Profile	
IP Rating	IP65 / IP54	
Maintenance	Front/Rear	
Certification	FCC, ETL, CE	



## AW Series Next-Gen

- Centimeter-Level Clarity, Pixel-Perfect Up Close
- IP65 Robust Protection, All-Weather Stability
- Smart O&M, Worry-Free Lifecycle
- Creative Modularity, Limitless Forms

### Specification

Parameters	AW2.5	AW2.8	AW3.9	Unit
Pixel Pitch	2.5	2.84	3.9	mm
Brightness	5000	5000	5500	nit
Power (Max/Avg)	530/177	560/187	590/197	W/m <sup>2</sup>
Refresh Rate		≥7680		Hz
Grayscale Level		16		bit
Contrast Ratio	4200:1	4500:1	4200:1	--
Cabinet Dimensions		500x500x99/19.69 x 19.69 x 3.90" 500x1000x99/ 19.69 x 39.37 x 3.90"		mm/inch
Module Dimensions		250x250/9.84 x 9.84"		mm/inch
Cabinet Weight		7.1kg/15.7lbs(500x500) 13.4kg/29.5lbs(500x1000)		kg/lbs
Cabinet Material		Die-cast Aluminum		--
Maintenance Method		Front and Rear Maintenance		--
Protection Rating		IP65/IP65		--